

FUEGO INDICATOR - MODEL: EIR2SF

In-ground Luminaires

WAC LIGHTING

Responsible Lighting®


项目名称:

灯位号:

产品图片



线图



产品描述

FUEGO Indicator 整体不锈钢材质，精工铸造，圆形外观，IP68 防护等级，可适用于水下环境，IK08 防冲击等级，可抗压 500kg。不锈钢弹片的设计可支持墙体或者筒灯式安装。

产品特性

- 主体材质: 整体不锈钢材质
- 光学系统: 透镜
- 表面处理: /
- 投射方向: /
- 配件/支架: /
- 安规认证: CQC
- 防护等级: IP68
- 绝缘等级: Class III
- 环境温度: -20°C~50°C

产品规格

- 光源类型: High Power
- 光源功率: 4W (Max)
- 光源光通量: 3000K 500lm ;4000K 500lm; Amber; Blue
- 光源寿命: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- 色温/显指: 3000K, Ra85 / 4000K , Ra85
- 光源色容差: 3 SDCM
- 输入电压: 9-15V/AC
- 调光控制: ON-OFF
- 产品重量: 约 0.7Kg, 不含包装

订购模型

Model	comment	Power (W)	LEDs (quantity)	Max Lumens (Lm)	Control Systems	Beam	CCT	Finish
EIR2S	F Frame	04 4(Max)	1	170	ET ON-OFF 9-15V/AC Power Supply	2 25°	30 3000K 40 4000K A Amber B Blue	SS Stainless Steel

示例: EIR2SF-04ET-240SS

WAC Lighting

www.waclighting.com (US)

www.waclighting.com.cn (China)

Headquarters

44 Harbor Park Drive • Port Washington, NY

Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)

14,Lane 299, Bi Sheng Road,Shanghai 201204

Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting 保留对产品进行不定期设计更新的权利。2018-07-11

FUEGO INDICATOR - MODEL: EIR2SF

In-ground Luminaires



WAC LIGHTING

Responsible Lighting®


项目名称:

灯位号:

配件

Item	Pic	Small Version
Single Directional (Round Frame)		EIR2SF-SDRF-SS
Double Directional (Round Frame)		EIR2SF-DDRF-SS

配光曲线@3000K数据



型号:	EIR2SF-04ET-230SS
光束角:	25°
系统功率:	6W (Max)
系统光通量:	170 lm
中心光强:	/
系统光效:	28 lm /W

WAC Lighting

www.waclighting.com (US)

www.waclighting.com.cn (China)

Headquarters

44 Harbor Park Drive • Port Washington, NY

Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)

14, Lane 299, Bi Sheng Road, Shanghai 201204

Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting 保留对产品进行不定期设计更新的权利。2018-07-11