

FUEGO COMPACT- MODEL: EIR*NF

In-ground Luminaires

WAC LIGHTING

Responsible Lighting®

项目名称:

灯位号:

产品图片

线图



产品描述

Fuego Compact 不锈钢材质灯身精加工，圆形外观，小巧精致，超薄的外观设计，IP67 / IP68 防护等级，IK08 防冲击等级，可抗压500kg，预埋筒安装、卡扣安装。

- 产品特性**

 - **主体材质:** 不锈钢灯身
 - **光学系统:** 透镜
 - **表面处理:** /
 - **投射方向:** /
 - **配件/支架:** 不锈钢卡扣/预埋筒
 - **安规认证:** CQC
 - **防护等级:** IP67 / IP68, IK08
 - **绝缘等级:** Class III
 - **环境温度:** -20°C~50°C
- 产品规格**

 - **开孔尺寸:** EIR2NF: $\varnothing$ 48mm ; EIR4NF: $\varnothing$ 51mm
 - **光源类型:** High Power LED
 - **光源功率:** 3W Max
 - **光源光通量:** 2700K 365lm /3000K 378lm /4000K 390lm
 - **光源寿命:** >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
 - **色温/显指:** 2700K / 3000K / 4000K , Ra90; RGBW
 - **光源色容差:** 3 SDCM (MONO) , 5 SDCM (RGBW)
 - **输入电压:** 12V-24V DC
 - **调光控制:** ON-OFF / 0-10V 调光控制 / DMX512 调光控制
 - **产品重量:** 约 0.2Kg, 不含包装

订购模型							
Model	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Finish	
EIR2NF-04	4(Max)	1	119	ET ON-OFF	W Wall Washer	27 2700K	SS Stainless Steel
				12-24V DC Power Supply	L Laser Blade		
				MT DMX512 Dimming	S 8°		
				12-24V DC Power Supply	1 10°		
				DT 0-10V Dimming	2 20°		
				12-24V DC Power Supply	3 30°	40 4000K	

示例: EIR2NF-04ET-W27SS

FUEGO COMPACT- MODEL: EIR*NF

In-ground Luminaires

WAC LIGHTING
Responsible Lighting®

项目名称:

灯位号:

Model	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Finish
EIR2NF-04	4(Max)	1	35	MT DMX512 Dimming 12-24V DC Power Supply	1 14° 2 24° F 16x23°	F3 RGBW (W3000K) F4 RGBW (W4000K) F6 RGBW (W5700K)	SS Stainless Steel

示例: EIR2NF-04MT-1F3SS


Model	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Finish
EIR4NF-04	4(Max)	1	119	ET ON-OFF 12-24V DC Power Supply MT DMX512 Dimming 12-24V DC Power Supply DT 0-10V Dimming 12-24V DC Power Supply	W Wall Washer L Laser Blade S 3° 1 10° 2 20° 3 30°	27 2700K 30 3000K 40 4000K	SS Stainless Steel

示例: EIR4NF-04ET-W27SS

Model	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Finish
EIR4NF-04	4(Max)	1	35	MT DMX512 Dimming 12-24V DC Power Supply	1 14° 2 24° F 16x23°	F3 RGBW (W3000K) F4 RGBW (W4000K) F6 RGBW (W5700K)	SS Stainless Steel

示例: EIR4NF-04MT-1F3SS

配件

Item	Description	Pic	Description Dimensions
EIR4NF-RC001	Recessed Casing		


FUEGO COMPACT- MODEL: EIR*NF
In-ground Luminaires

WAC LIGHTING
Responsible Lighting®


项目名称:

灯位号:


配光曲线@3000K数据




型号 :	EIR4NF-04MT-1F3SS EIR2NF-04MT-1F3SS
光束角 :	14°
系统功率 :	4 W
系统光通量 :	34.8 lm
中心光强 :	269 cd
系统光效 :	8.6 lm/W




型号 :	EIR4NF-04MT-2F3SS EIR2NF-04MT-2F3SS
光束角 :	24°
系统功率 :	3.9 W
系统光通量 :	30.5 lm
中心光强 :	123.6 cd
系统光效 :	7.7 lm/W




型号 :	EIR4NF-04MT-FF3SS EIR2NF-04MT-FF3SS
光束角 :	16×23°
系统功率 :	3.9 W
系统光通量 :	32.3 lm
中心光强 :	172.2 cd
系统光效 :	8.3 lm/W




型号 :	EIR4NF-04MT-L30SS EIR2NF-04MT-L30SS
光束角 :	8.4×77.2°
系统功率 :	4.4 W
系统光通量 :	57.8 lm
中心光强 :	233.2 cd
系统光效 :	13.3 lm/W




型号 :	EIR4NF-04MT-130SS EIR2NF-04MT-130SS
光束角 :	10°
系统功率 :	4 W
系统光通量 :	122.3 lm
中心光强 :	1977 cd
系统光效 :	30 lm/W



型号 :	EIR4NF-04MT-230SS EIR2NF-04MT-230SS
光束角 :	20°
系统功率 :	4 W
系统光通量 :	80.6 lm
中心光强 :	474.9 cd
系统光效 :	19.8 lm/W



型号 :	EIR4NF-04MT-330SS EIR2NF-04MT-330SS
光束角 :	28.3°
系统功率 :	4.1 W
系统光通量 :	82.6 lm
中心光强 :	276.2 cd
系统光效 :	20.3 lm/W



型号 :	EIR4NF-04MT-S30SS EIR2NF-04MT-S30SS
光束角 :	8°
系统功率 :	4.1 W
系统光通量 :	133.6 lm
中心光强 :	3481 cd
系统光效 :	32.6 lm/W

FUEGO COMPACT- MODEL: EIR*NF


In-ground Luminaires

WAC LIGHTING

Responsible Lighting®

项目名称:

灯位号:



型 号 :	EIR4NF-04MT-W30SS
	EIR2NF-04MT-W30SS
光 束 角 :	WALL WASHER
系 统 功 率 :	4.4 W
系 统 光 通 量 :	77.1 lm
中 心 光 强 :	300 cd
系 统 光 效 :	17.6 lm/W